

TOP OF ROOT BALL SHALL  
MATCH EXISTING FINISHED  
GRADE

MINIMUM 3" SHREDDED  
PROCESSED HARDWOOD MULCH

DO NOT REMOVE BALL MATERIAL.  
ONLY BINDING MATERIAL FROM  
STEM SHALL BE CUT.  
REMOVE TWINE FROM ROOT COLLAR  
AND BRANCHES AND TURN  
BURLAP TOP DOWN

EXISTING FINISHED GRADE

BACKFILL WITH EXCAVATED SOIL AND OR  
PREPARED SOIL

LOOSEN SOIL ALONG PLANTING HOLE  
BOTTOM

UNDISTURBED SUBGRADE  
OR COMPACTED SUBGRADE

NOTES:

1. FINAL BALL ELEVATION AND PLANTER BED GRADING AS DIRECTED BY PLAN.
2. WHEN SOIL CONDITIONS WITH POOR DRAINAGE ARE DISCOVERED,  
NOTIFY VILLAGE REPRESENTATIVE.
3. LANDSCAPE CONTRACTOR SHALL SUGGEST SOLUTION FOR DRAINAGE IMPROVEMENTS

## SHRUB PLANTING DETAIL



**northbrook**  
Public Works Department

DATE	REVISIONS
4-30-20	Revised Notes
4-1-21	Added Plan Note

**STANDARD DETAIL**  
**G-2 (02)**